

	Standard	Result
Size		1211.2 mm x 169.8 mm
Thickness	ISO 24346	4.5 mm
Wear layer	ISO 24340	0.3 mm
Locking mechanism ¹		2G™ angling installation system
Surface treatment		K-Guard+ PU coating
Guarantee ²	Residential	20 years
Bevelled edge		No
Mass per unit area	ISO 23997	6575 g/m ²
Standards	EN 16511	Pass (Multilayer modular floorcovering panels)
Classification	ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _R -s1
Staining resistance	EN 438-2	Pass (Grade 5)
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 13329 Annex E	Pass (>1200 cycles)
Furniture chair leg	EN 424	Pass (No visible damage)
Dimensional stability	BS EN ISO 23999	Pass (< 0.25%)
Swelling	ISO 24336	Pass (0.2%)
Acoustic impact noise reduction	EN ISO 10140-1:2016	ΔL _w = 19 dB
Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
Impact resistance	EN 13329 Annex F	Pass (> 1800 mm)
Thermal resistance	ISO 8302	0.052 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ³	EN 13893 DIN 51130	DS R9
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive		None required, Please install according to our installation instructions.
Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 ISO 14001 / ISO 9001	Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. Manufactured to quality and environment management systems standard
Recycling		Suitable
Phthalate free		Yes

¹ 2G™ is a patented technology invented by Välinge Innovation AB. The 2G™ word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² Subject to terms. Please see our website.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:
Call: 01386 820210
Email: info@palioexpress.com
Visit: www.palioexpress.com



EN 14041: 2004 (DOP 2020/PRC/EN/01)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23
Manufactured to EN 16511



BS EN 14041: 2004 (DOP 2021/UKCA/PRC/01)
Approved body 0321
Floor coverings (internal)
ISO 10874 Class 23
Manufactured to EN 16511



	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	PVP142-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	26
	PVP143-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	20
	PVP144-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	34
	PVP145-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	27
	PVP146-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	27
	PVP147-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	38
	PVP148-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	21
	PVP149-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	46
	PVP150-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	25
	PVP151-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	9