





























## Technical data

	Standard	Result	Product	Size (mm)	LRV
 Size		See separate table	RCT6301	307 x 600	27
 Locking system		2G	RCT6302	307 x 600	51
 Thickness	ISO 24346	6.5 mm	RCT6303	307 x 600	40
 Wear layer	ISO 24340	0.55 mm	RCT6304	307 x 600	11
 Surface treatment		PU coating	RCP6502	1220 x 179	11
 Warranty	Commercial	15 years *	RCP6503	1220 x 179	28
	Domestic	Lifetime warranty*	RCP6504	1220 x 179	26
 Bevelled edge		Thread	RCP6505	1220 x 179	23
 Mass per unit area	ISO 23997	7480 g m <sup>-2</sup>	RCP6506	1220 x 179	10
 Standards	EN 16511	Pass:-Multilayer modular floorcovering panels	RCP6507	1220 x 179	17
 Classification	ISO 10874 Commercial	33:-commercial heavy	RCP6508	1220 x 179	41
	ISO 10874 domestic	23:-Domestic heavy	RCP6509	1220 x 179	12
 Reaction to fire	EN13501-1	B <sub>fl</sub> -s1			
 Staining	EN 438-2	pass (grade 5)			
 Light fastness	EN ISO 105-B02	pass ≥6			
 Abrasion resistance	EN13329 Annex E	pass 4000 cycles			
 Furniture chair leg	EN 424	pass (no visible damage)			
 Dimensional stability	BS EN ISO 23999	pass ≤0.25%			
 Swelling	ISO 24336	pass (0.2 %)			
 Acoustic impact noise reduction	EN ISO 10140-1:2016 and )	ΔL <sub>w</sub> = 19 dB			
	EN ISO 10140-3:2010+A1:2015 )	ΔL <sub>LIN</sub> = 11 dB			
 Indentation-residual	ISO 24343-1	Pass ≤ 0.1mm			
 Impact resistance	EN13329 Annex F	pass ≥1800 mm			
 castor chair continuous use	ISO 4918/ EN425	pass 25 000 cycles			
 Thermal resistance	ISO 8302	0,052 m <sup>2</sup> K/W			
		suitable for underfloor heating max 27 °C			
 Slip resistance**	EN 13893	D5			
	DIN 51130	R10			
	BS7976	63 (dry), 36 (wet)			
 Light reflectance value (LRV)	BS 8493:2008+A1:2010	See separate table			
 VOC emission	French VOC regulation (ISO 16000)	A+			
 Adhesive		None required;please install according to our installation instructions.			
 Recycling		Suitable			
 Phthalate free		Yes			

\*Subject to terms. Please see our website.

\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

Call: 01386 820200

For ROI call: 01 6569887

Email: [info@palioflooring.com](mailto:info@palioflooring.com)

Visit: [www.palioflooring.com](http://www.palioflooring.com)

Manufactured to ISO9001

