



Technical Data



| | Standard | Result |
|--|---------------------------------------|--|
| Size | EN ISO 24342 | See separate table |
| Thickness | EN ISO 24346 | 2.5 mm |
| Wear layer | EN ISO 24340 | 0.55 mm |
| Surface treatment | | PU coating |
| Guarantee | Light industrial | 15 years* |
| | Commercial | 15 years* |
| | Residential | Lifetime guarantee* |
| Bevelled edge | | No |
| Mass | EN ISO 23997 | 4120 g/m ² |
| Standards | EN 649/ EN ISO 10582 | Pass |
| Classification | EN 685/EN ISO 10874- Light industrial | 42:Light industrial moderate |
| | EN 685/EN ISO 10874- Commercial | 33: Commercial general |
| | EN 685/EN ISO 10874- Domestic | 23: Domestic heavy |
| Reaction to fire | EN 13501-1 | B _{fl} -s1 |
| Staining resistance | EN ISO 26987/EN 423 | Excellent |
| Light fastness | EN ISO 105-B02 | 7 |
| Abrasion resistance | EN 649/ EN ISO 10582 | Group T |
| | EN ISO 10582 | Type 1 |
| Flexibility | EN ISO 24344 | Pass |
| Dimensional stability | EN 434/ EN ISO 23999 | ≤ 0.25% |
| Acoustic Impact noise reduction | EN ISO 717-2 / EN ISO 140-8 | ΔL _w = 2 dB |
| Electrical behaviour body voltage | EN 1815 | Pass |
| Indentation - residual | EN 433/ EN ISO 24343-1 | Pass ≤ 0.1mm |
| Castor chair continuous use | EN 425/ISO 4918 | Pass |
| Thermal resistance | EN 12664 | 0.0126 m ² K/W Suitable for underfloor heating. Max 27°C |
| Slip resistance** | BS 7976 | See separate table |
| | DIN 51130 | R10 |
| | DIN 51097 | See separate table |
| | EN 13893 | DS |
| Light reflectance value (LRV) | BS 8493:2008+A1:2010 | See separate table |
| VOC emission | ISO 16000 | Indoor Air Comfort Gold |
| Adhesive | Karndean Universal | Yes |
| | Acrylic | Yes |
| | Epoxy | Yes |
| | High Temperature | Yes |
| | Pressure sensitive | Yes |
| Recycling | | Suitable |
| Phthalate free | | Yes |

| Product | Size (mm) | Slip Resistance | | | LRV |
|---------|------------------------|-----------------|---------------|-----------|-----|
| | | BS 7976 (dry) | BS 7976 (wet) | DIN 51097 | |
| PVP5142 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 26 |
| PVP5143 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 20 |
| PVP5144 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 34 |
| PVP5145 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 27 |
| PVP5146 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 27 |
| PVP5147 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 38 |
| PVP5148 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 21 |
| PVP5149 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 46 |
| PVP5150 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 25 |
| PVP5151 | 1219.2 x 177.8(48"x7") | 61 | 33 | B | 9 |
| PVT5201 | 457.2 x 304.8(18"x12") | 64 | 34 | C | 6 |
| PVT5202 | 457.2 x 304.8(18"x12") | 66 | 27 | C | 50 |
| PVT5203 | 457.2 x 304.8(18"x12") | 64 | 40 | C | 41 |
| PVT5204 | 457.2 x 304.8(18"x12") | 64 | 40 | C | 33 |

*Subject to terms. Please see our website.

**Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:
 Call: 01386 820110
 Email: info@palioflooring.com
 Visit: www.palioflooring.com

For ROI call: 01 6569887

Manufactured to ISO9001



EN 14041:2004 (DOP 2019/PGluedown0.55/EN/01)
 Notified body 0321
 Floor Coverings (Internal)
 ISO 10874 Class 23/33/42
 Manufactured to ISO 10582