



	Standard	Result	Product	Size (mm)	LRV
Size	EN ISO 24342	See separate table	LLP142	1050 X 250	26
Thickness	EN ISO 24346	4.5 mm	LLP143	1050 X 250	20
Wear layer	EN ISO 24340	0.55 mm	LLP144	1050 X 250	34
Surface treatment		PU coating	LLP145	1050 X 250	27
Guarantee	Light industrial	15 years*	LLP146	1050 X 250	27
	Commercial	15 years*	LLP147	1050 X 250	38
	Residential	Lifetime guarantee*	LLP148	1050 X 250	21
Bevelled edge		No	LLP149	1050 X 250	46
Mass	EN ISO 23997	7470 g/m ²	LLP150	1050 X 250	25
Standards	EN 649/EN ISO 10582	Pass	LLP151	1050 X 250	9
Classification	EN 685/EN ISO 10874- Light industrial	42: Light industrial general	LLT208	610 x 500	66
	EN 685/EN ISO 10874- Commercial	33: Commercial heavy	LLT209	610 x 500	44
	EN 685/EN ISO 10874- Domestic	23: Domestic heavy	LLT210	610 x 500	23
Reaction to fire	EN 13501-1	B _{f1} -s1	LLT211	610 x 500	10
Staining resistance	EN ISO 26987/EN 423	Excellent			
Light fastness	EN ISO 105-B02	7			
Abrasion resistance	EN 649	Group T			
	EN ISO 10582	Type 1			
Flexibility	EN ISO 24344	Pass			
Dimensional stability	EN 434/ EN ISO 23999	≤ 0.10%			
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 13 dB			
Indentation - residual	EN 433/EN ISO 24343-1	Pass ≤ 0.1mm			
Castor chair continuous use	EN 425/ISO 4918	Pass			
Thermal resistance	ISO 8302	0.0245 m ² K/W Suitable for underfloor heating. Max 27°C			
Slip resistance**	DIN 51130	R10			
	EN 13893	DS			
Light reflectance value (LRV)	BS 8493:2008+A1:2010	See separate table			
VOC emission	ISO 16000	Indoor Air Comfort Gold			
Adhesive		Please refer to our installation instructions.			
Recycling		Suitable			
Phthalate free		Yes			

*Subject to terms. Please see our website.

**Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Call: 01386 820200

For ROI call: 01 6569887

Email: info@palioflooring.com

Visit: www.palioflooring.com

Manufactured to ISO9001



EN 14041:2004 (DOP 2017/PLL/EN/01)
Notified body 0321
Floor Coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582

