

## Technical Data



	Standard	Result
<b>Size</b>	EN ISO 24342	See separate table
<b>Locking system</b>		2G
<b>Thickness</b>	EN ISO 24346	4.5 mm
<b>Wear layer</b>	EN ISO 24340	0.4 mm
<b>Surface treatment</b>		PU coating
<b>Guarantee</b>	Light industrial	12 years*
	Commercial	12 years*
	Domestic	Lifetime guarantee*
<b>Bevelled edge</b>		No
<b>Mass</b>	EN ISO 23997	9050 g/m <sup>2</sup>
<b>Standards</b>	EN 649/ EN ISO 10582	Pass
<b>Classification</b>	EN 685/EN ISO 10874- Light industrial	41: Light industrial moderate
	EN 685/EN ISO 10874- Commercial	32: Commercial general
	EN 685/EN ISO 10874- Domestic	23: Domestic heavy
<b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> -s1
<b>Staining resistance</b>	EN 423	Class 0
<b>Light fastness</b>	EN ISO 105-B02	≥7
<b>Abrasion resistance</b>	EN 649	Group T
	EN ISO 10582	Type 1
<b>Dimensional stability</b>	EN 434/ EN ISO 23999	Pass
<b>Acoustic Impact noise reduction</b>	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 4 dB
<b>Electrical behaviour body voltage</b>	EN 1815	Pass
<b>Indentation - residual</b>	EN 433/EN ISO 24343-1	Pass ≤ 0.1mm
<b>Castor chair continuous use</b>	EN 425/ ISO 4918	Pass
<b>Thermal resistance</b>	ISO 8302	0.0197 m <sup>2</sup> K/W
		Suitable for underfloor heating. Max 27°C
<b>**Slip resistance</b>	BS 7976	See separate table
	DIN 51130	R10
	DIN 51097	See separate table
<b>Light reflectance value (LRV)</b>	BS 8493:2008+A1:2010	See separate table
<b>VOC emission</b>	French VOC regulation (ISO 16000)	A+
<b>Adhesive</b>		None required; please install according to our installation instructions.
<b>Recycling</b>		Suitable

\*Subject to terms. Please see our website.

\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

### For more information:


call: 01386 820200

For ROI call: 01 6569887

Email: [info@palioflooring.com](mailto:info@palioflooring.com)

Visit: [www.palioflooring.com](http://www.palioflooring.com)

Manufactured to ISO9001



Product	Size (mm)	Slip Resistance			LRV
		BS 7976 (dry)	BS 7976 (wet)	DIN 51097	
CP4502	1220 x 179	63	38	B	11
CP4503	1220 x 179	63	38	B	28
CP4504	1220 x 179	63	38	B	26
CP4505	1220 x 179	63	38	B	23
CP4506	1220 x 179	63	38	B	10
CP4507	1220 x 179	63	38	B	17
CP4508	1220 x 179	63	38	B	41
CP4509	1220 x 179	63	38	B	12
CT4301	600 X 307	52	30	C	27
CT4302	600 X 307	52	30	C	51
CT4303	600 X 307	52	30	C	40
CT4304	600 X 307	52	30	C	11