

	STANDARD	RESULT	
	Size	EN ISO 24342	See separate table
	Thickness	EN ISO 24346	4.5 mm
	Wear layer	EN ISO 24340	0.55 mm
	Surface treatment		K-Guard+® PU coating
	Warranty ¹	Light industrial	15 years
		Commercial	15 years
		Residential	20 years
	Bevelled edge		None
	Mass per unit area	EN ISO 23997	7470 g/m ²
	Standards	EN ISO 10582	Pass
	Classification	EN ISO 10874 - Light industrial	42: Light industrial general
		EN ISO 10874 - Commercial	33: Commercial heavy
		EN ISO 10874 - Domestic	23: Domestic heavy
	Reaction to fire	EN 13501-1	Bfl-S1
	Staining resistance	EN ISO 26987	Excellent
	Light fastness	EN ISO 105-B02	Pass (≥ 7)
	Abrasion resistance	EN ISO 10582	Type 1
	Flexibility	EN ISO 24344	Pass
	Dimensional stability	EN ISO 23999	Pass (≤ 0.10%)
	Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔLw = 13 dB
	Indentation - residual	EN ISO 24343-1	Pass (≤ 0.1 mm)
	Castor chair continuous use	ISO 4918	Pass
	Thermal resistance	ISO 8302	0.0245 m ² K/W
		Underfloor heating	Suitable. Max 27°C
	Slip resistance ²	EN 13893	DS
		EN 16165 Annex B/DIN 51130	R10
	Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
	Adhesive		Refer to installation instructions
	Environmental	Indoor Air Comfort	Gold
		Floorscore SCS-EC10.3-2014 v4.0	Certified
		ISO 14001 / ISO 9001	Manufactured in certified facilities
	Partnerships	Royal Institute of British Architects	



Technical Datasheet

Palio LooseLay



	CE / DOP	EN 14041	DOP 2017/PLL/EN/02
	CA / DOP	BS EN 14041	DOP 2021/UKCA/PLL/01
	Recycling		Suitable
	Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.



Technical Datasheet

Palio LooseLay



Plank/Tile	Size (mm)	Size (in)	Box qty (m ²)	Box qty (pieces)	Slip Resistance
Plank	1050.0 x 250.0	41.34" x 9.84"	3.15	12	R10
Tiles	500.0 x 610.0	19.69" x 24.02"	3.05	10	R10

Light Reflectance Values can be found on the following page/s.

