

























	Standard	Result
 Size	EN ISO 24342	See separate table
 Thickness	EN ISO 24346	2.0 mm
 Wear layer	EN ISO 24340	0.3 mm
Surface treatment		PU coating
Guarantee¹	Commercial	10 years
	Residential	20 years
 Bevelled edge		No
 Mass per unit area	EN ISO 23997	3360 g/m ²
 Standards	EN 649/EN ISO 10582	Pass
 Classification	EN 685/EN ISO 10874 - Commercial	31: Commercial moderate
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987/EN 423	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 649/EN ISO 10582	Group T
	EN ISO 10582	Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN 434/EN ISO 23999	Pass
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	EN 425/ISO 4918	Pass
 Thermal resistance	EN 12664	0.0107 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance²	EN 13893	DS
	DIN 51130	R10
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive	Karndean Universal	Yes
	Silane	Yes
	Pressure Sensitive	Yes
 Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.


² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820110 | ROI: 01 6569887

Email: info@palioflooring.com


Visit: www.palioflooring.com



21



20





	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	PVP142	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	26
	PVP143	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	20
	PVP144	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	34
	PVP145	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	27
	PVP146	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	27
	PVP147	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	38
	PVP148	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	21
	PVP149	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	46
	PVP150	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	25
	PVP151	1219.2 x 177.8	48.0" x 7.0"	4.769	22 Planks	R10	9
Stone Designs	PVT1201	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	6
	PVT1202	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	50
	PVT1203	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	41
	PVT1204	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	33