



	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2.0 mm
Wear layer	EN ISO 24340	0.3 mm
Surface treatment		PU coating
Guarantee	Light industrial	n/a
	Commercial	10 years*
	Domestic	Lifetime guarantee*
Bevelled edge		No
Mass	EN ISO 23997	3190 g/m ²
Standards	EN 649/ EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874- Light industrial	n/a
	EN 685/EN ISO 10874- Commercial	31: Commercial moderate
	EN 685/EN ISO 10874- Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B ₁ -s1
Staining resistance	EN 423	Class 0
Light fastness	EN ISO 105-B02	≥6
Abrasion resistance	EN 649/ EN ISO 10582	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/ EN ISO 23999	Pass
Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ EN ISO 24343-1	Pass ≤ 0.1mm
Castor chair continuous use	EN 425/OSO 4918	Pass
Thermal resistance	ISO 8302	0.0100 m ² K/W
		Suitable for underfloor heating. Max 27°C
**Slip resistance	BS 7976	See separate table
	DIN 51130	R10
	DIN 51097	See separate table
	EN 13893	D5
Light reflectance value (LRV)	BS 8493:2008+A1:2010	See separate table
VOC emission	French VOC regulation (ISO 16000)	A+
	Karndean Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature	Yes
Adhesive	Pressure sensitive	Yes
	Recycling	Suitable

*Subject to terms. Please see our website.

**Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

Product	Size (mm)	Slip Resistance			LRV
		BS 7976 (dry)	BS 7976 (wet)	DIN 51097	
PVP142	1219.2 x 177.8	61	33	B	26
PVP143	1219.2 x 177.8	61	33	B	20
PVP144	1219.2 x 177.8	61	33	B	34
PVP145	1219.2 x 177.8	61	33	B	27
PVP146	1219.2 x 177.8	61	33	B	27
PVP147	1219.2 x 177.8	61	33	B	38
PVP148	1219.2 x 177.8	61	33	B	21
PVP149	1219.2 x 177.8	61	33	B	46
PVP150	1219.2 x 177.8	61	33	B	25
PVP151	1219.2 x 177.8	61	33	B	9
PVT1201	457.2 x 304.8	64	34	C	6
PVT1202	457.2 x 304.8	66	27	C	50
PVT1203	457.2 x 304.8	64	40	C	41
PVT1204	457.2 x 304.8	64	40	C	33

For more information:

Call: 01386 820200 For ROI call: 01 6569887

Email: info@palioflooring.com

Visit: www.palioflooring.com

Manufactured to ISO9001

